

# SAFETY DATA SHEET



Date Issued : 6/28/2013  
SDS No : 123754  
Date Revised : 9/11/2013  
Revision No : 1

## Duratec, Additive, High Gloss, Clear, 904-001, Gallon Can

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Duratec, Additive, High Gloss, Clear, 904-001, Gallon Can

**GENERAL USE:** Color: Clear.

**PRODUCT CODE:** 123754

#### MANUFACTURER

Fiberglass Coatings Inc.  
4301A 34th Street North  
St. Petersburg, FL 33714  
**Emergency Phone:** ChemTel(800)255-3924  
**Customer Service:** 800-272-7890  
**E-Mail:** www.fgci.com

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

Chem-Tel (800) 255-3924

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Acute Toxicity (Oral), Category 5  
Skin Irritation, Category 3  
Eye Irritation, Category 2B

##### Physical:

Flammable Liquids, Category 2

#### GHS LABEL



Flame



Exclamation  
mark

#### HAZARD STATEMENTS

H225: Highly flammable liquid and vapor.  
H315: Causes skin irritation.  
H320: Causes eye irritation.  
H303: May be harmful if swallowed.

#### PRECAUTIONARY STATEMENT(S)

##### Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
P233: Keep container tightly closed.  
P240: Ground/bond container and receiving equipment.

- P241: Use explosion-proof electrical/ventilating/lighting/ equipment.  
 P242: Use only non-sparking tools.  
 P243: Take precautionary measures against static discharge.  
 P270: Do not eat, drink or smoke when using this product.  
 P264: Wash thoroughly after handling.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P337+P313: If eye irritation persists: Get medical advice/attention.  
 P332+P313: If skin irritation occurs: Get medical advice/attention.  
 P370+P378: In case of fire: Use appropriate extinguishing media (see Section 5).  
 P330: Rinse mouth.  
 P362: Take off contaminated clothing and wash before reuse.

**Storage:**

- P403+P235: Store in a well-ventilated place. Keep cool.

**Disposal:**

- P501: Dispose of contents/container in accordance with all Federal, State, and local regulations.

**EMERGENCY OVERVIEW**

**PHYSICAL APPEARANCE:** Clear, Colorless Liquid. Styrene odor.

**IMMEDIATE CONCERNS: Flammable Liquid and Vapor.** Causes eye, gastrointestinal and severe skin irritation. Aspiration Hazard which can lead to fatal chemical pneumonitis.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Can cause eye irritation. Symptoms include: stinging, tearing, redness, and swelling of the eyes.

**SKIN:** Can cause skin irritation. Symptoms may include redness, burning, drying and cracking of the skin, burns and other skin damage.

**INGESTION:** May be harmful if swallowed. Symptoms include: gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration Hazard. Can cause chemical pneumonitis which can be fatal.

**INHALATION:** Symptoms are similar to that of colds, be wary if cold like symptoms occur during handling. Symptoms include: nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headaches.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Vol. %	CAS
Styrene	33.81	100-42-5
2-butanone	14.18	78-93-3

**4. FIRST AID MEASURES**

**EYES:** Flush eyes for at least 15 minutes, holding eyelids open. If easily accomplished, check for and remove contact lenses. Seek immediate medical attention.

**SKIN:** Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**INGESTION:** Aspiration hazard. If swallowed, Do NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

**INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

## 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Category 2 Flammable Liquid

**EXTINGUISHING MEDIA:** Use dry chemical, CO<sub>2</sub>, water spray/fog (not jet), or foam

**EXPLOSION HAZARDS: Flammable Liquid.** Vapor may form explosive mixture with air. Can polymerize when heated. Combustion can produce toxic gases. Vapors are heavier than air, can travel along the ground or through ventilation systems, and be ignited by sparks, flames or static discharge.

**FIRE FIGHTING PROCEDURES:** Evacuate any non-essential personnel. Extinguish all ignition sources if safe to do so. Use water to cool exposed containers and structures until fire is out. Avoid spreading burning material with water used for cooling purposes.

**FIRE FIGHTING EQUIPMENT:** Full Bunker gear(helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus (SCBA).

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Extinguish all near by ignition sources. Stop leak if it can be done safely. Prevent from entering waterways and sewers. Absorb with non-combustible material and transfer into appropriate disposal container.

**LARGE SPILL:** Follow procedure for small spills. Dike ahead of spill to contain material. Water mist may be used to disperse vapors. Notify proper authorities if the spill cannot be contained. Follow Federal, State, and local regulations for disposal.

**GENERAL PROCEDURES:** Always ensure proper ventilation from any spill. Respirators or SCBA are required if permissible exposure limits are exceeded due to inadequate general ventilation. All spills should be contained as best as possible. All chemical spills should be assumed to be hazardous to the environment to ensure safety.

## 7. HANDLING AND STORAGE

**HANDLING:** Avoid ignition sources (flame, spark, smoking, etc) in use or handling areas. Use explosion proof electrical equipment. Ensure proper electrical grounding procedures are in place. Provide sufficient ventilation. Always wear proper personal protection equipment when handling.

**STORAGE:** Store in a cool, dry, well-ventilated area, away from any sources of ignition and incompatible materials. Keep all equipment grounded to avoid static sparking. Keep container closed when not being used.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Styrene	TWA	50		20	85
	STEL	100		40	170
2-butanone	TWA	200	590	200	590
	STEL	300		300	885

**ENGINEERING CONTROLS:** Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits (PEL/TLV). Any installed emergency eye wash station or safety showers should be located near the work area.

#### **PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Chemical splash goggles and/or face shield. Always use proper eye protection around the work area.

**SKIN:** Wear impermeable gloves. Clothing should limit skin exposure. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product. Maintain eyewash and shower station near work area in case of exposure.

**RESPIRATORY:** Vapor respirator may be required if exposure limits are exceeded. Use a NIOSH approved respirator or equivalent when required. Proper mechanical ventilation should be installed to ensure the exposure levels are below the allowable thresholds (PEL/TLV).

**WORK HYGIENIC PRACTICES:** Never eat or drink in areas where the chemical is being used. Wash hands after handling to limit exposure.

### **9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Liquid

**ODOR:** Styrene Odor

**APPEARANCE:** Colorless Liquid

**COLOR:** Clear

**pH:** No data available.

**PERCENT VOLATILE:** 33

**FLASH POINT AND METHOD:** -6.67°C (20°F)

**FLAMMABLE LIMITS:** 1% to 10%

**AUTOIGNITION TEMPERATURE:** 759.2°C (404°F)

**Notes:** Autoignition temp listed for Methyl Ethyl Ketone (CAS: 78-93-3)(Lowest listed autoignition temperature). Unknown autoignition for mixture.

**VAPOR PRESSURE:** No data available.

**VAPOR DENSITY:** > 1 (Air =1)

**BOILING POINT:** 79°C (175°F) to 146°C (295°F)

**MELTING POINT:** No data available.

**SOLUBILITY IN WATER:** Insoluble.

**EVAPORATION RATE:** < 1 (Ethyl Ether = 1)

**SPECIFIC GRAVITY:** 1.02

**(VOC):** 4.100 lbs/gal

**Notes:** Assumes all Styrene monomer will evaporate.

### **10. STABILITY AND REACTIVITY**

**STABLE:** Yes

**HAZARDOUS POLYMERIZATION:** Yes

**POLYMERIZATION:** Under normal conditions of use, hazardous reactions will not occur. Extreme heat can cause rapid, uncontrolled polymerization.

**CONDITIONS TO AVOID:** Avoid contact with incompatible materials and ignition sources / heat.

**INCOMPATIBLE MATERIALS:** Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Aliphatic Amines, and Oxidizers.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Styrene	5000 mg / kg (Rat)	> 2000 mg / kg (dermal Rabbit)	11.8 mg/L (4h)
2-butanone	2737 mg / kg (Rat)	6480 mg/kg (Rabbit)	320 ppm (4h)

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** Environmental studies have not been performed for this mixture.

**ECOTOXICOLOGICAL INFORMATION:** Do NOT discharge into sewers or waterways. Numerical data is not available. Assumed to be toxic to aquatic life and the environment for safety.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be in accordance with all Federal, State, and local regulations. Empty containers may still be considered dangerous due to residual vapors/liquid/dust.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Paint related material.

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** 1263

**PACKING GROUP:** II

### AIR (ICAO/IATA)

**SHIPPING NAME:** Paint related material.

**UN/NA NUMBER:** 1263

**PRIMARY HAZARD CLASS/DIVISION:** 3

**PACKING GROUP:** II

### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Paint related material.

**UN/NA NUMBER:** 1263

**PRIMARY HAZARD CLASS/DIVISION:** 3

## PACKING GROUP: II

## 15. REGULATORY INFORMATION

## UNITED STATES

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** Fire Hazard, Immediate (acute) Health Hazard, Chronic (Delayed) Health Hazard, Reactivity.

**TITLE III NOTES:** Components meeting the requirements are listed.

## 16. OTHER INFORMATION


**PREPARED BY:** Fiberglass Coatings, Inc (HE)

**REVISION SUMMARY:** This MSDS replaces the 7/5/2013 MSDS. Revised: **Section 8:** WORK HYGIENIC PRACTICES. **Section 9:** MELTING POINT, pH, VAPOR PRESSURE. **Section 14:** AIR (ICAO/IATA) - SPECIAL PROVISIONS DOT (DEPARTMENT OF TRANSPORTATION) - PROPER SHIPPING NAME ROAD AND RAIL (ADR/RID), ROAD AND RAIL (ADR/RID) ( VEHICLE FOR TANK, PROPER SHIPPING NAME, UN NUMBER, PACKING GROUP ), VESSEL (IMO/IMDG) ( PRIMARY HAZARD CLASS/DIVISION, PACKING GROUP, UN/NA NUMBER ). **Section 16:** NFPA CODES ( HEALTH, REACTIVITY ).

## HMIS RATING

HEALTH		2
FLAMMABILITY		3
PHYSICAL HAZARD		2
PERSONAL PROTECTION	H	

## NFPA CODES



**MANUFACTURER DISCLAIMER:** This information is compiled from sources believed reliable as of the date of issue, it is provided in good faith and correct to the best of our knowledge. No warranty, guarantee, or representation is made as to the sufficiency of the information for the safe use of the product nor to relieve the end user of their own Federal, State, and Local regulatory compliance requirements.