

SAFETY DATA SHEET



Date Issued : 6/28/2013
SDS No : 123756
Date Revised : 8/7/2015
Revision No : 3

Duratec, Coating or Additive, Crystal Clear, 904-040, Gallon Can

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Duratec, Coating or Additive, Crystal Clear, 904-040, Gallon Can
GENERAL USE: Color: Clear.
PRODUCT CODE: 123756

MANUFACTURER

Fiberglass Coatings Inc.
4301A 34th Street North
St. Petersburg, FL 33714
Customer Service: (800) 272-7890
E-Mail: www.fgci.com
Emergency Contact: Chem-Tel
Emergency Phone: (800) 255-3924

24 HR. EMERGENCY TELEPHONE NUMBERS

Chem-Tel (800) 255-3924

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 5
Skin Irritation, Category 3
Eye Irritation, Category 2B

Physical:

Flammable Liquids, Category 2

GHS LABEL



Flame



Exclamation
mark

HAZARD STATEMENTS

H225: Highly flammable liquid and vapor.
H315: Causes skin irritation.
H320: Causes eye irritation.
H303: May be harmful if swallowed.

PRECAUTIONARY STATEMENT(S)

Prevention:

P210: Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
P233: Keep container tightly closed.

P240: Ground container and receiving equipment to prevent static discharge.
 P241: Use explosion-proof electrical, ventilating, and lighting equipment.
 P242: Use only non-sparking tools.
 P280: Wear protective gloves, protective clothing, eye protection and face protection.
 P243: Take precautionary measures against static discharge.
 P264: Wash skin thoroughly after handling.
 P270: Do not eat, drink or smoke when using this product.

Response:

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
 P370+P378: In case of fire: Use appropriate extinguishing media (see Section 5).
 P301+P312: IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell.
 P330: Rinse mouth.
 P332+P313: If skin irritation occurs: Get medical attention.
 P362: Take off contaminated clothing and wash before reuse.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313: If eye irritation persists: Get medical advice.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

P501: Dispose of container and its contents in accordance with all Federal, State, and local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear, Colorless Syrup-like Liquid.

IMMEDIATE CONCERNS: **Flammable Liquid and Vapor.** Causes eye, gastrointestinal and severe skin irritation. Aspiration Hazard which can lead to fatal chemical pneumonitis.

POTENTIAL HEALTH EFFECTS

EYES: Can cause eye irritation. Symptoms include: stinging, tearing, redness, and swelling of the eyes.

SKIN: Can cause skin irritation. Symptoms may include redness, burning, drying and cracking of the skin, burns and other skin damage.

INGESTION: May be harmful if swallowed. Symptoms include: gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration Hazard. Can cause chemical pneumonitis which can be fatal.

INHALATION: Symptoms are similar to that of colds, be wary if cold like symptoms occur during handling. Symptoms include: nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headaches.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
Styrene	< 35	100-42-5
2-butanone	< 4.3	78-93-3

COMMENTS: The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

EYES: Flush eyes with water for at least 15 minutes, holding eyelids open. Remove contact lenses if present and easy to do so.

Seek immediate medical attention.

SKIN: Immediately flush with plenty of soap and water. Remove and dispose of contaminated clothing. Seek medical attention.

INGESTION: Aspiration hazard. If swallowed, Do NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Category 2 Flammable Liquid

EXTINGUISHING MEDIA: Use dry chemical, CO₂, water spray/fog (not jet), or foam

FIRE FIGHTING PROCEDURES: Evacuate any non-essential personnel. Extinguish all ignition sources if safe to do so. Use water to cool exposed containers and structures until fire is out. Avoid spreading burning material with water used for cooling purposes.

FIRE FIGHTING EQUIPMENT: Full Bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus (SCBA).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Extinguish all nearby ignition sources. Stop leak if it can be done safely. Prevent from entering waterways and sewers. Absorb with non-combustible material and transfer into appropriate disposal container.

LARGE SPILL: Use a shovel to put the material in to a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system.

GENERAL PROCEDURES: Always ensure proper ventilation from any spill. Respirators or SCBA are required if permissible exposure limits are exceeded due to inadequate general ventilation. All spills should be contained as best as possible. All chemical spills should be assumed to be hazardous to the environment to ensure safety.

7. HANDLING AND STORAGE

HANDLING: Avoid ignition sources (flame, spark, smoking, etc) in use or handling areas. Use explosion proof electrical equipment. Ensure proper electrical grounding procedures are in place. Provide sufficient ventilation. Always wear proper personal protection equipment when handling.

STORAGE: Store in a cool, dry, well-ventilated area, away from any sources of ignition and incompatible materials. Keep all equipment grounded to avoid static sparking. Keep container closed when not being used.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Styrene	TWA	50		20	85
	STEL	100		40	170
2-butanone	TWA	200	590	200	590
	STEL	300		300	885

ENGINEERING CONTROLS: Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits (PEL/TLV). Any installed emergency eye wash station or safety showers should be located near the work area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical splash goggles and/or face shield. Always use proper eye protection around the work area.

SKIN: Wear impermeable gloves. Clothing should limit skin exposure. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product. Maintain eyewash and shower station near work area in case of exposure.

RESPIRATORY: Vapor respirator may be required if exposure limits are exceeded. Use a NIOSH approved respirator or equivalent when required. Proper mechanical ventilation should be installed to ensure the exposure levels are below the allowable thresholds (PEL/TLV).

WORK HYGIENIC PRACTICES: Never eat or drink in areas where the chemical is being used. Wash hands after handling to limit exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid.

ODOR: Styrene Odor

APPEARANCE: Liquid, Color is dependent on color in name (variety of colors from clear to black) (Section 1: Trade Name)

COLOR: Varying color from colorless clear to black.

PERCENT VOLATILE: 35

FLASH POINT AND METHOD: -4°C (20°F)

FLAMMABLE LIMITS: 1.1% to 10%

AUTOIGNITION TEMPERATURE: 404°C (759.2°F)

Notes: Autoignition temp listed for Methyl Ethyl Ketone (CAS: 78-93-3)(Lowest listed autoignition temperature). Unknown autoignition for mixture.

VAPOR DENSITY: > 1 (Air =1)

BOILING POINT: 79°C (175°F) to 146°C (295°F)

MELTING POINT: No data available.

SOLUBILITY IN WATER: Insoluble.

EVAPORATION RATE: < 1 (Ethyl Ether = 1)

SPECIFIC GRAVITY: 1.06

(VOC): 3.500 lbs/gal

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: Yes

POLYMERIZATION: Under normal conditions of use, hazardous reactions will not occur. Extreme heat can cause rapid, uncontrolled polymerization.

CONDITIONS TO AVOID: Avoid contact with incompatible materials and ignition sources / heat.

INCOMPATIBLE MATERIALS: Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Aliphatic Amines,

Oxidizers and Reactive Metals (Aluminum, Magnesium, etc.).

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Styrene	5000 mg / kg (Rat)	> 2000 mg / kg (dermal Rabbit)	11.8 mg/L (4h)
2-butanone	2737 mg / kg (Rat)	6480 mg / kg (Rabbit)	320 ppm (4h)

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Environmental studies have not been performed for this mixture.

ECOTOXICOLOGICAL INFORMATION: Do NOT discharge into sewers or waterways. Numerical data is not available. Assumed to be toxic to aquatic life and the environment for safety.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be in accordance with all Federal, State, and local regulations. Empty containers may still be considered dangerous due to residual vapors/liquid/dust.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Paint

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: 1263

PACKING GROUP: II

AIR (ICAO/IATA)

SHIPPING NAME: Paint

UN/NA NUMBER: 1263

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: II

VESSEL (IMO/IMDG)

SHIPPING NAME: Paint

UN/NA NUMBER: 1263

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: II

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Fire Hazard, Immediate (acute) Health Hazard, Reactivity.

TITLE III NOTES: Components meeting the requirements are listed.


16. OTHER INFORMATION

PREPARED BY: Fiberglass Coatings, Inc (HE)

REVISION SUMMARY: This MSDS replaces the 9/5/2014 MSDS. Revised: **Section 14:** DOT (DEPARTMENT OF TRANSPORTATION) - PROPER SHIPPING NAME.

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY		3
PHYSICAL HAZARD		2
PERSONAL PROTECTION		H

NFPA CODES

MANUFACTURER DISCLAIMER: This information is compiled from sources believed reliable as of the date of issue, it is provided in good faith and correct to the best of our knowledge. No warranty, guarantee, or representation is made as to the sufficiency of the information for the safe use of the product nor to relieve the end user of their own Federal, State, and local regulatory compliance requirements.