

# SAFETY DATA SHEET



Date Issued : 4/7/2014  
SDS No : 125301

## Superbond Epoxy Fast Curing Agent

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Superbond Epoxy Fast Curing Agent  
**GENERAL USE:** Adhesive  
**PRODUCT CODE:** 125301

#### MANUFACTURER

Fiberglass Coatings Inc.  
4301A 34th Street North  
St. Petersburg, FL 33714  
**Customer Service:** (800) 272-7890  
**E-Mail:** [www.fgci.com](http://www.fgci.com)  
**Emergency Contact:** Chem-Tel  
**Emergency Phone:** (800) 255-3924

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Skin Corrosion, Category 1  
Eye Corrosion, Category 1  
Respiratory Tract Irritation, Category 1  
Skin Sensitization, Category 1

##### Environmental:

Aquatic Toxicity (Acute), Category 1  
Aquatic Toxicity (Chronic), Category 4

#### GHS LABEL



Corrosion



Health  
hazard



Environment

**SIGNAL WORD:** DANGER

#### HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.  
H305: May be harmful if swallowed and enters airways.  
H317: May cause an allergic skin reaction.  
H412: Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENT(S)

**Prevention:**

P260: Do not breathe fumes.  
 P280: Wear protective gloves, protective clothing, eye protection and face protection.  
 P264: Wash skin thoroughly after handling.  
 P273: Avoid release to the environment.

**Response:**

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.  
 P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
 P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
 P310: Immediately call a POISON CENTER or physician.  
 P363: Wash contaminated clothing before reuse.  
 P391: Collect spillage.

**Storage:**

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

**Disposal:**

P501: Dispose of container and its contents in accordance with all Federal, State, and local regulations.

**EMERGENCY OVERVIEW**

**PHYSICAL APPEARANCE:** Amber paste.

**IMMEDIATE CONCERNS:** Causes eye and skin damage. Causes respiratory tract irritation. May be harmful if swallowed. May cause target organ damage based on animal data.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Corrosive, contact causes severe eye burns.

**SKIN:** Corrosive, causes skin burning.

**INGESTION:** Harmful if swallowed. May cause burns to mouth and esophagus.

**INHALATION:** Inhalation may cause respiratory tract irritation. Aspiration can cause significant lung damage.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Wt.%	CAS
Nonylphenol	30 - 55	84852-15-3
Non Hazardous Mineral Fillers	> 7	N/A
Polyamide Resin (Trade Secret)	6 - 12	N/A
Benzyl Alcohol	3 - 8	100-51-6
Mixed Cycloaliphatic Amines	2 - 6	N/A
DETA	9 - 13	111-40-0
4,4'-isopropylidenediphenol	5 - 10	80-05-7

**COMMENTS:** The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**EYES:** Flush eyes for at least 15 minutes, holding eyelids open. Do not use eye ointment. If easily accomplished, check for and remove contact lenses. If contact lenses cannot be removed, seek immediate medical attention.

**SKIN:** Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**INGESTION:** Aspiration hazard. If swallowed, Do NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

**INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

**NOTES TO PHYSICIAN:** Treat symptomatically. May require supportive therapy as needed. Severe exposure should be followed by at least 48 hour monitoring.

## 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Not categorized as Flammable by GHS standards. However, can still be ignited by external sources above flash point.

**EXTINGUISHING MEDIA:** Use dry chemical, CO<sub>2</sub>, water spray/fog (not jet), or foam

**HAZARDOUS COMBUSTION PRODUCTS:** Produces carbon oxides (CO, CO<sub>2</sub>).

**FIRE FIGHTING PROCEDURES:** Evacuate any non-essential personnel. Extinguish all ignition sources if safe to do so. Use water to cool exposed containers and structures until fire is out. Avoid spreading burning material with water used for cooling purposes.

**FIRE FIGHTING EQUIPMENT:** Full Bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus (SCBA).

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Extinguish all nearby ignition sources. Stop leak if it can be done safely. Prevent from entering waterways and sewers. Absorb with non-combustible material and transfer into appropriate disposal container.

**LARGE SPILL:** Use a shovel to put the material in to a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system.

## 7. HANDLING AND STORAGE

**HANDLING:** Avoid ignition sources (flame, spark, smoking, etc) in use or handling areas. Use explosion proof electrical equipment. Ground all equipment containing this material. Do not ingest or breathe vapors/fumes. Avoid contact with eyes and skin. Always wear proper PPE when handling. Provide sufficient ventilation. A NIOSH respirator is required if permissible exposure limits are exceeded.

**STORAGE:** Store in a cool, dry, well-ventilated area, away from any sources of ignition and incompatible materials. Keep all equipment grounded to avoid static sparking. Keep container closed when not being used.

**SPECIAL SENSITIVITY:** Avoid storage in direct sunlight.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Nonylphenol	TWA	N/E [1]	[1]	N/E	
Non Hazardous Mineral Fillers	TWA		6	[2]	10 [2]
Benzyl Alcohol	TWA	10	44		
DETA	TWA			1 Skin	4
4,4'-isopropylidenediphenol	TWA	N/E [1]	[1]		
<b>Footnotes:</b>					
1. N/E = Not Established					
2. Inhalable					

**ENGINEERING CONTROLS:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below any exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Chemical splash goggles and/or face shield. Always use proper eye protection around the work area.

**SKIN:** Wear impermeable gloves. Clothing should limit skin exposure. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product. Maintain eyewash and shower station near work area in case of exposure.

**RESPIRATORY:** No respiratory protection is usually required under normal conditions of use.

**PROTECTIVE CLOTHING:** Clothing should be applicable for the job at hand to protect the skin from repeated exposure to the material.

**WORK HYGIENIC PRACTICES:** Never eat or drink in areas where the chemical is being used. Wash hands after handling to limit exposure.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Paste.

**ODOR:** Ammonia like odor.

**APPEARANCE:** Amber paste.

**pH:** Suspected.

**Notes:** Alkaline

**PERCENT VOLATILE:** No data available.

**FLASH POINT AND METHOD:** 101°C (213°F) Closed Cup

**FLAMMABLE LIMITS:** Not yet Determined

**AUTOIGNITION TEMPERATURE:** No data available.

**VAPOR PRESSURE:** 3 mm Hg @ 20 C

**VAPOR DENSITY:** < 1 (Air =1)

**BOILING POINT:** > 392°C (200°F)

**FREEZING POINT:** No data available.

**MELTING POINT:** No data available.

**SOLUBILITY IN WATER:** Slightly soluble

**EVAPORATION RATE:** Not Available

**DENSITY:** 0.93 at 20°C

**SPECIFIC GRAVITY:** 1.02 (Water = 1)

**VISCOSITY:** No data available.

**(VOC):** No data available.

## 10. STABILITY AND REACTIVITY

**STABLE:** Yes

**HAZARDOUS POLYMERIZATION:** No

**POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid contact with incompatible materials and ignition sources / heat.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**INCOMPATIBLE MATERIALS:** Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Aliphatic Amines, and Oxidizers.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Nonylphenol	1412 mg / kg (oral Rat)	2031 mg / kg (dermal Rabbit)	
Non Hazardous Mineral Fillers	> 5000 mg / kg (Rat)	> 5000 mg / kg (dermal Rabbit)	2.08 mg/L (4h)
Benzyl Alcohol	1230 mg / kg (Rat)	2000 mg / kg (Rabbit)	> 4.178 mg/L (4h) aerosol (Rat)
Mixed Cycloaliphatic Amines		> 1000 mg / kg	
DETA	1080 mg / kg (Rat)	1090 mg / kg (Rabbit)	> 0.07 to 0.3 mg/L (4h)
4,4'-isopropylidenediphenol	> 2000 mg / kg (Rat)	3000 mg / kg (Rabbit)	

**EYE EFFECTS:** Corrosive to the eyes.

**SKIN EFFECTS:** Corrosive to the skin.

### CARCINOGENICITY

**Notes:** Not considered carcinogenic by OSHA, NTP, or IARC.

**TARGET ORGANS:** May cause damage to the following organs: kidneys.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** Considered very toxic to aquatic organism, may cause long-term adverse effects in the aquatic environment. Not readily biodegradable. Shows high bioaccumulation potential. Water polluting material. May be harmful to the environment if released in large quantities.

**BIOACCUMULATION/ACCUMULATION:** Bioaccumulation: high potential, not readily biodegradable  
Bioconcentration factor (BCF): 740, LogPow: 5.4

### AQUATIC TOXICITY (ACUTE):

#### Exposure :: Species :: Result

3H Static :: Bacteria :: 950 mg/L (EC50)

96 Flow-Thru :: Daphnia :: 0.596 mg/L (EC50)

48H :: Daphnia :: 0.14 mg/L (EC50)

48H Static :: Daphnia :: 0.085 mg/L (EC50)

96H Flow-Thru :: Daphnia :: 0.0207 mg/L (EC50)

72H Static :: Algae :: 1.3 mg/L (EC50)

96H Static :: Algae :: 0.41 mg/L (EC50)

**Notes:** Values listed for Nonylphenol (CAS# 84852-15-3)

**GENERAL COMMENTS:** No data is available on the product itself.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be in accordance with all Federal, State, and local regulations. Empty containers may still be considered dangerous due to residual vapors/liquid/dust.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Amines, Liquid, Corrosive n.o.s.

**TECHNICAL NAME:** Nonylphenol

**PRIMARY HAZARD CLASS/DIVISION:** 8

**UN/NA NUMBER:** 2735

**PACKING GROUP:** III

**MARINE POLLUTANT #1:** Nonylphenol

### ROAD AND RAIL (ADR/RID)

**PROPER SHIPPING NAME:** Amines, Liquid, Corrosive n.o.s.

**UN NUMBER:** 2735

**HAZARD CLASS:** 8

**PACKING GROUP:** III

### AIR (ICAO/IATA)

**SHIPPING NAME:** Amines, Liquid, Corrosive n.o.s.

**TECHNICAL NAME:** Nonylphenol

**UN/NA NUMBER:** 3145

**PRIMARY HAZARD CLASS/DIVISION:** 8

**PACKING GROUP:** III

**VESSEL (IMO/IMDG)**

**SHIPPING NAME:** Amines, Liquid, Corrosive n.o.s.

**TECHNICAL NAME:** Nonylphenol

**UN/NA NUMBER:** 2735

**PRIMARY HAZARD CLASS/DIVISION:** 8

**PACKING GROUP:** III

**MARINE POLLUTANT #1:** Listed.

**15. REGULATORY INFORMATION**

**UNITED STATES**

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HAZARD CATEGORIES:** Immediate (acute) Health Hazard, Chronic (Delayed) Health Hazard.

**FIRE:** No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

**TITLE III NOTES:** Components meeting the requirements are listed.

**302/304 EMERGENCY PLANNING**

**EMERGENCY PLAN:** Not Listed.

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

**CERCLA REGULATORY:** Not Listed.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA REGULATORY:** All items are TSCA listed

**CALIFORNIA PROPOSITION 65:** This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

**OSHA HAZARD COMM. RULE:** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

**CANADA**

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** Listed.


**WHMIS CLASS:** Class D-2B: Material causing other toxic effects (Toxic).  
Class E: Corrosive material

**16. OTHER INFORMATION**

**PREPARED BY:** BC

**HMIS RATING**

<b>HEALTH</b>	*	<b>3</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		

**NFPA CODES**

**HMIS RATINGS NOTES:** The customer is responsible for determining the PPE code for this material.

**MANUFACTURER DISCLAIMER:** This information is compiled from sources believed reliable as of the date of issue, it is provided in good faith and correct to the best of our knowledge. No warranty, guarantee, or representation is made as to the sufficiency of the information for the safe use of the product nor to relieve the end user of their own Federal, State, and local regulatory compliance requirements.