

SAFETY DATA SHEET



Date Issued : 4/15/2014
SDS No : 128602
Date Revised : 6/12/2015
Revision No : 1

Gelcoat Putty, White

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Gelcoat Putty, White
PRODUCT CODE: 128602

MANUFACTURER

Fiberglass Coatings Inc.
4301A 34th Street North
St. Petersburg, FL 33714
Customer Service: (800) 272-7890
E-Mail: www.fgci.com
Emergency Contact: Chem-Tel
Emergency Phone: (800) 255-3924

24 HR. EMERGENCY TELEPHONE NUMBERS

Chem-Tel (800) 255-3924

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation, Category 2
Eye Irritation, Category 2A
Acute Toxicity (Inhalation), Category 5

Environmental:

Aquatic Toxicity, Category 2

Physical:

Flammable Liquids, Category 3

GHS LABEL



Flame



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H226: Flammable liquid and vapor.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H333: May be harmful if inhaled.
H401: Toxic to aquatic life.

PRECAUTIONARY STATEMENT(S)**Prevention:**

- P202: Do not handle until all safety precautions have been read and understood.
 P210: Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
 P223: Keep away from any possible contact with water, because of violent reaction and possible flash fire.
 P240: Ground container and receiving equipment to prevent static discharge.
 P241: Use explosion-proof electrical, ventilating, and lighting equipment.
 P280: Wear protective gloves, protective clothing, eye protection and face protection.
 P264: Wash skin thoroughly after handling.
 P273: Avoid release to the environment.

Response:

- P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
 P302+P352: IF ON SKIN: Wash with plenty of soap and water.
 P332+P313: If skin irritation occurs: Get medical attention.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313: If eye irritation persists: Get medical advice.
 P308+P313: IF exposed or concerned: Get medical advice

Storage:

- P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

- P501: Dispose of container and its contents in accordance with all Federal, State, and local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: White Liquid, Styrene Odor.

IMMEDIATE CONCERNS: Flammable liquid and vapor. Vapors may travel to a source and flash back. May cause respiratory tract, eye and skin irritation.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: May cause moderate to severe skin irritation. Prolonged exposure may cause skin burns.

INGESTION: May be harmful if swallowed. Symptoms include: gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration Hazard. Can cause chemical pneumonitis which can be fatal.

INHALATION: Breathing of high vapor concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Vapors expected to be slightly irritating.

CARCINOGENICITY: IARC: Classified 2B (possible for humans)

ROUTES OF ENTRY: Skin, Inhalation, Eyes

TARGET ORGAN STATEMENT: Liver, Central nervous system.

COMMENTS: This product contains non-hazardous components which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Styrene	30 - 40	100-42-5
Polyester Resin (Trade Secret)	20 - 30	XXXXXX
Non Hazardous Fillers	30 - 50	XXXXXX

COMMENTS: The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

EYES: Flush eyes with water for at least 15 minutes, holding eyelids open. Remove contact lenses if present and easy to do so. Seek immediate medical attention.

SKIN: Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

INGESTION: Aspiration hazard. If swallowed, Do NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

NOTES TO PHYSICIAN: Styrene: Do not induce vomiting. Gastrointestinal decontamination in accidental petroleum distillate ingestions is not recommended, because of the severe aspiration hazard. Gastric lavage is indicated in those patients who require decontamination. Be sure that an endotracheal tube is in place prior to lavage; use cuffed tubes in patients over 7 years of age. All contaminated clothing should be removed, and contaminated skin areas washed with lipophilic soap, or green soap, and water. If ingested, cardiac and respiratory status must be continuously monitored. Be prepared to give oxygen and, if necessary, intubate. A chest x-ray should be taken immediately after stabilization of breathing and circulation to document aspiration and detect the presence of pneumothorax.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Category 3 Flammable Liquid

EXTINGUISHING MEDIA: Small Fire: Water spray or fog, Alcohol-resistant foam, Dry chemical powder, carbon dioxide, sand or earth can be used for small fires.

Large Fire: Water spray or fog, Alcohol-resistant foam. Do not discharge extinguishing waters into the aquatic environment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide. Carbon dioxide (CO₂). Formaldehyde vapors.

EXPLOSION HAZARDS: Vapours may form explosive mixture with air. Vapors are heavier than air and may spread along floors. Vapor may travel considerable distance to source of ignition and flash back.

FIRE FIGHTING PROCEDURES: Cool containers with flooding quantities of water until well after fire is out to avoid pressure build up, autoignition or explosion.

FIRE FIGHTING EQUIPMENT: Full Bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus (SCBA).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb with an inert material and put the spilled material in an appropriate waste disposal container.

LARGE SPILL: Flammable liquid. Keep away from heat and other sources of ignition. Eliminate all ignition sources. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV.

7. HANDLING AND STORAGE

HANDLING: Use only in a well-ventilated area. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid direct contact (eye, skin, inhalation, ingestion) when possible. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Take precautionary measures against static discharges. Wash clothing before reuse. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.

STORAGE: Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Styrene	TWA	50		20	85
	STEL	100		40	170

ENGINEERING CONTROLS: Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits (PEL/TLV). Any installed emergency eye wash station or safety showers should be located near the work area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical splash goggles. Always use proper eye protection around the work area.

SKIN: Wear solvent resistant gloves (consult safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910. 134.

WORK HYGIENIC PRACTICES: Minimize exposure in accordance with good hygiene practice

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid.

ODOR: Solvent Odor.

FLASH POINT AND METHOD: 28°C (83°F) Closed Cup

FLAMMABLE LIMITS: 1.1% to 12.5%

BOILING POINT: 100°C (212°F) to 145°C (293°F)

SOLUBILITY IN WATER: Negligible.

SPECIFIC GRAVITY: 1.268 (Water = 1)

(VOC): 35.590

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under recommended storage conditions.

POLYMERIZATION: Under normal conditions of use, hazardous reactions will not occur. Extreme heat can cause rapid, uncontrolled polymerization.

CONDITIONS TO AVOID: Avoid contact with incompatible materials and ignition sources / heat.

INCOMPATIBLE MATERIALS: Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Aliphatic Amines, and Oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Styrene	5000 mg / kg (Rat)	> 2000 mg / kg (dermal Rabbit)	11.8 mg/L (4h)

EYE EFFECTS: Causes eye irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury.

SKIN EFFECTS: Causes mild skin irritant.

Prolonged or repeated exposure: may cause defatting of the skin, which can lead to dermatitis.

CARCINOGENICITY

IARC: Group 2B - Possibly carcinogenic for humans.

NTP: Reasonably anticipated to be a human carcinogen

OSHA: Possible select carcinogen.

Notes: Listed by IARC as possibly carcinogenic to humans (Group 2B), based on limited evidence of carcinogenicity in humans and experimental animals.

TARGET ORGANS: Cardiac sensitization. Nervous system. Nasal cavity. Lung. Eye. Skin.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Toxic to fish, invertebrates and microorganisms, however, substantial aquatic exposure is not expected based on the volatile nature of this material.

BIOACCUMULATION/ACCUMULATION: No data available.

AQUATIC TOXICITY (ACUTE): Acute toxicity to fish. Toxicity to aquatic plants.

96-HOUR LC₅₀: 4-10 mg / L (Fathead Minnow)

48-HOUR EC₅₀: 3-7 mg/L (Daphnia Magna)

96-HOUR EC₅₀: 0.1-1. mg/L (Algae)

Notes: Information given is based on data on the components and the ecotoxicology of similar products.

GENERAL COMMENTS: No data is available on the product itself.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be in accordance with all Federal, State, and local regulations. Empty containers may still be considered dangerous due to residual vapors/liquid/dust.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Resin Solution

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: 1866

PACKING GROUP: III

NAERG: 127

VESSEL (IMO/IMDG)

SHIPPING NAME: Resin Solution

UN/NA NUMBER: 1866

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: III

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Fire Hazard, Immediate (acute) Health Hazard, Chronic (Delayed) Health Hazard, Reactivity.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** Yes **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: Styrene

TITLE III NOTES: Components meeting the requirements are listed.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: Not Listed.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Styrene

CERCLA RQ: 0.1 % de minimis concentration

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All items are TSCA listed

CLEAN AIR ACT

40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: Listed.

CLEAN WATER ACT: Listed.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Listed.

WHMIS CLASS: B2 Flammable Liquid, D2A Very Toxic Material, D2B Toxic Material.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components are listed.

16. OTHER INFORMATION


PREPARED BY: BC

REVISION SUMMARY: This MSDS replaces the 4/15/2014 MSDS.

HMIS RATING

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		2
PERSONAL PROTECTION		

NFPA CODES



HMIS RATINGS NOTES: The customer is responsible for determining the PPE code for this material.

MANUFACTURER DISCLAIMER: This information is compiled from sources believed reliable as of the date of issue, it is provided in good faith and correct to the best of our knowledge. No warranty, guarantee, or representation is made as to the sufficiency of the information for the safe use of the product nor to relieve the end user of their own Federal, State, and local regulatory compliance requirements.